



### KEY BENEFITS AND FEATURES

- Excellent weather resistance.
- Protects substrates from Carbonization
- Elastic nature with crack bridging properties
- Outstanding resistance to the attack of salty and acidified atmosphere.
- Prevents efflorescence
- Single Component- easy to apply.

### USAGE

- To all external and internal wall surfaces.
- Can be applied over variety of substrates like concrete, masonry and asbestos.

### DIRECTIONS FOR USE

**Surface Preparation:** Substrates shall be clean, sound and free from contaminants such as oil, grease, and any existing loose or flaking paintwork. Cracks or holes if any must be filled with **TEC<sup>R</sup> KRACK FILLER**. High pressurewater jetting may be deemed necessary for heavily contaminated surfaces. New concrete surfaces shall be cured with water for a minimum of 14 days before the application Dilute 1 kg with 250 ml of water for the first coat and after an interval 1 hour apply the second coat with a dilution of 200 ml of water.

**Cleaning:** Clean all the equipments with water immediately after use.

### Precautions:

Direct contact with skin or eyes should be avoided. Use of gloves, goggles and other protective gear is mandatory. In case of accidental eye contact thorough water washing is advised. This should be followed up with professional medical assistance.

### TECHNICAL DATA

Colour	White, Terracotta, Off-white (Other colors on request)
Finish	Semi – Matt
Coverage	4 to 4.5 m per coat/per kg
Touch dry	30 min to 120 minute
Thorough dry	4 to 6 hours
DFT	250 microns

### PACKING:

1 kg and 15 kg containers



#### **OTHER PRODUCTS:**

Techny manufactures lot more range of other products for construction and repair applications. They include admixtures for concrete, mortars, block making etc, waterproof and damp proof coating systems, Repair and rehabilitations products, Grouts and Anchors, Protective, Decorative and Corrosion prevention coatings, Epoxy Flooring systems, Industrial flooring systems and Tiling aids. For more details refer Separate Product brochures.

Every reasonable precaution is taken in the manufacture of the Techny products to ensure that they comply with high standards of quality. The recommendations and properties of the products are based upon what is believed to be the most reliable information available and are not intended as recommendations which infringe other patents. Although all Techny products are subject to rigid quality tests, no specific guarantee can be given, because results depend not only on quality but also on other factors beyond our control. We therefore welcome consultation in the event of doubt about application performance etc but do not accept any liability either directly or indirectly arising from the use of the products whether used as per its specifications or advice or otherwise. All transactions shall be subject to our terms of sale, delivery and payment. The leaflet super cedes the previous one and any new issue may take place without notice to supercede this edition as and when it becomes necessary.