



KEY BENEFITS AND FEATURES

- It is non-shrinkable and will not crack.
- It is anti-fungus and will not promote fungus growth
- It is tough and has high abrasion resistance.
- It has high bond strength.
- It is water repellent.
- IT HAS BUILT IN FLEXIBILITY to with stand forces created by expansion and contraction of tiles.
- Available in all tile colours and shades.

DIRECTIONS FOR USE

SURFACE PREPARATION: Before grouting remove excess mortars and other dust and loose particles with a damp sponge.

MIXING: Mix 2 to 3 parts of Tec[®] Tile 12 to one part of water by volume to form a paste like grout. Wait for few minutes before applying the grout.

APPLICATION: Apply to the tile joints with a squeegee or spatula.

CLEANING: Remove surplus paste with a wet cloth. Polish the tiles with dry cloth when the job is over.

For addition of Tec[®] Tile 12 LQ grout admixture will greatly enhance the physical and water resistant property of the cured grout.

TECHNICAL DATA:

Physical State	Powder
Color	Available in more than 40 colors
Shelf Life	Maximum of 1 year from date of manufacture in unopened package
Coverage	1kg for 4sq metres (43 Sq ft.) Using standard 152mm x 152mm tiles.

PACKAGING:

Available in: 1 kg retail pack and if required can be supplied in 25 kgs project packing

TEC[®] TILE 12 - General purpose tile joint grout is available in various matching shades.



Certified:
ISO 9001 (QMS) & ISO
14001 (EMS)



OTHER PRODUCTS

Techny manufactures lot more range of other products for construction and repair applications. They include admixtures for concrete, mortars, block making etc, waterproof and damp proof coating systems, Repair and rehabilitations products, Grouts and Anchors, Protective, Decorative and Corrosion prevention coatings, Epoxy Flooring systems, Industrial flooring systems and Tiling aids. For more details refer Separate Product brochures.

Every reasonable precaution is taken in the manufacture of the Techny products to ensure that they comply with high standards of quality. The recommendations and properties of the products are based upon what is believed to be the most reliable information available and are not intended as recommendations which infringe other patents. Although all Techny products are subject to rigid quality tests, no specific guarantee can be given, because results depend not only on quality but also on other factors beyond our control. We therefore welcome consultation in the event of doubt about application performance etc but do not accept any liability either directly or indirectly arising from the use of the products whether used as per its specifications or advice or otherwise. All transactions shall be subject to our terms of sale, delivery and payment. The leaflet supercedes the previous one and any new issue may take place without notice to supercede this edition as and when it becomes necessary.

TECHNICAL DATA SHEET
REVISED - February, 2010

CORPORATE OFFICE:

No.24, Patel Street, Ayyappa Nagar, Tiruchirapalli-620 021, Tamil Nadu, India
Phone : 0431 2458519 Fax No : 0431 2458590 Email : info@technychemistry.co.in
Web : www.technychemistry.co.in